



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|---------------------------|------------------------|--|
| FINISH: | Plaster | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Plaster | GROSS WEIGHT: | 2.28 (kg) |
| DIMENSIONS: | H: 325mm W: 190mm D: 55mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Wall Mount - Vertical | IP RATING: | IP20 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230V |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Suitable for mounting on flammable materials |


LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | Mid-Power LED | MACADAM ELIPSE: | 3-Step |
| MAXIMUM WATTAGE: | 2 x 6.4W | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | Not Applicable |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | To Be Advised | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 2700 (K) | AVERAGE LIFESPAN: | 60,000 (Hrs) |
| CRI: | 80 | L70: | To Be Advised |
| R9: | To Be Advised | | |

ELECTRICAL

| | | | |
|-------------------------------|----------------|-----------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | 50/60 (Hz) |
| DIMMABLE: | Yes | DRIVER / BALLAST VOLTAGE: | 100-240 (V) |
| DIMMING METHOD: | 1 - 10 (V) | DRIVER AVERAGE LIFESPAN: | 50,000 (Hrs) |
| DRIVER OUTPUT CURRENT: | 700 (mA) | EFFICACY: | To Be Advised |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | Yes (Integral) |

ADDITIONAL INFORMATION



THIS PRODUCT CAN BE SPRAY PAINTED

PRODUCT ELEVATIONS

